
Intel Xeon (X14) | 1U Rackmount | Server

Supermicro SYS-122C-TN

Intel Xeon (X14) · 1U Rackmount Server

Specifications reproduced from the official Supermicro product page, as of 17 Nov 2026. Taknet Systems (Thailand) is a Supermicro Authorized Distributor.



Form Factor	**1U Rackmount**
CPU	**Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores**
GPU	**Up to 3 single-width GPUs**
Memory	**Max Memory (1DPC): Up to 4TB 6400MT/s ECC DDR5 RDIMM**

Key Features

- Designed for Data Center Modular Hardware Systems (DC-MHS) to simplify CSP deployments and serviceability
- Optimized power & balanced performance for cloud applications
- Server management flexibility with OpenBMC

Form Factor	1U Rackmount
Platform	Intel Xeon (X14)
CPU	Dual Socket E2 (LGA-4710) Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores
Max GPU Count	Up to 3 single-width GPUs
Supported GPU	NVIDIA PCIe: A1000, L4
Memory	Slot Count: 32 DIMM slots Max Memory (1DPC): Up to 4TB 6400MT/s ECC DDR5 RDIMM
Drive Bays	Default: Total 12 bays12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays
Fans	Up to 8x 4cm heavy duty fans with optimal fan speed control
Power Supply	2x 1000W Redundant (1 + 1) Titanium Level (96%) power supplies

Full Specifications — SYS-122C-TN

Product SKUs

Part numbers	SYS-122C-TN

Motherboard

Motherboard	Super X14DBHM

Processor

CPU	Dual Socket E2 (LGA-4710) Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores
Core Count	P-cores: Up to 86C/172T; Up to 336MB Cache per CPU E-cores: Up to 144C/144T; Up to 108MB Cache per CPU
Note	Supports up to 350W TDP CPUs (Air Cooled)* *Air Cooled CPUs with TDP over 250W only supported under specific conditions. Contact a Supermicro representative for details.

GPU

Max GPU Count	Up to 3 single-width GPUs
Supported GPU	NVIDIA PCIe: A1000, L4 View GPU Options

System Memory

Memory	Slot Count: 32 DIMM slots Max Memory (1DPC): Up to 4TB 6400MT/s ECC DDR5 RDIMM Max Memory (1DPC): Up to 1TB 8000MT/s ECC DDR5 MRDIMM Max Memory (2DPC): Up to 8TB 6000MT/s ECC DDR5 RDIMM View Memory Options
Memory Voltage	1.1V

On-Board Devices

NVMe	NVMe; RAID 0/1/5/10 support(VROC HW key required) View NVMe Options
Network Connectivity	Via AIOM View AIOM Options View AOC Options

Input / Output

LAN	1 RJ45 1 GbE Dedicated BMC LAN port
USB	1 USB 2.0 Type-A port (Rear) 1 USB 3.2 Gen1 Type-A port (Rear)

Video	1 VGA port (Rear)
TPM	1 TPM header

System BIOS

BIOS Type	AMI 64MB SPI Flash ROM

Management

Software	SuperCloud Composer® (SCC) Supermicro Server Manager (SSM) Super Diagnostics Offline (SDO) Supermicro Thin-Agent Service (TAS) SuperServer Automation Assistant (SAA) New!
Power configurations	ACPI Power Management

Security

Hardware	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
Features	Cryptographically Signed Firmware Secure Boot Secure Firmware Updates Automatic Firmware Recovery Supply Chain Security: Remote Attestation Runtime BMC Protections System Lockdown

Certifications

Operating Systems	ESXi 8.0 U3, ESXi 9.0, Oracle Linux 9.4, RHEL 9.4, RHEL 10.0, Windows Server 2022, Windows Server 2025 View all OS Compatibility and Certification Matrix

Chassis

Form Factor	1U Rackmount
Model	CSE-DC101TS-R000NP

Dimensions and Weight

Height	1.7" (43.6 mm)
Width	17.2" (438.4 mm)
Depth	29.7" (755.1 mm)
Package	7.28" (H) x 22.83" (W) x 42.5" (D)

Weight	Gross Weight: 41 lbs (18.6 kg) Net Weight: 31 lbs (14.1 kg)
Palletized Packing (W x H x L)	49.6" (1260 mm) x 4.7" (120 mm) x 44.5" (1130 mm)
Available Color	Silver

Front Panel

Buttons	Power On/Off UID button
LED	HDD activity LAN1 activity LAN2 activity Power Fail LED Power status System information

Expansion Slots

PCI-Express (PCIe) Configuration	Default2 PCIe 5.0 x16 LP slots 1 PCIe 5.0 x8 LP slot 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible) 2 PCIe 5.0 x16 LP slots 1 PCIe 5.0 x8 LP slot 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible) View AOC Options

Drive Bays / Storage

Drive Bays Configuration	Default: Total 12 bays12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays 12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) View NVMe Options
M.2	2 M.2 PCIe 5.0 x2 NVMe slots (M-key 22110(default)/2280; VROC required for RAID) View M.2 Options

System Cooling

Fans	Up to 8x 4cm heavy duty fans with optimal fan speed control
Air Shroud	2 Air Shrouds

Power Supply

2x 1000W Redundant (1 + 1) Titanium Level (96%) power supplies

Dimension (WxHxL)	73.5 x 40 x 185 mm
Input	800W: 100-127Vac / 50-60Hz 1000W: 200-240Vac / 50-60Hz

+12V	Max: 66.7A (100Vac-127Vac) Max: 83A (200Vac-240Vac)
12V SB	Max: 2.1A
Output Type	Backplanes (gold finger)
Certification	Titanium Level [Test Report]

2x 1200W Redundant (1 + 1) Titanium Level (96%) power supplies

Dimension (WxHxL)	73.5 x 40 x 185 mm
Input	1200W: 100-240Vac / 50-60Hz 1200W: 0240Vdc / 50-60Hz (for CCC only)
+12V	Max: 100A / Min: 0A (100Vac-240Vac)
12V SB	Max: 4A / Min: 0A
Output Type	Backplanes (gold finger)

2x 1600W Redundant (1 + 1) Titanium Level (96%) power supplies

Dimension (WxHxL)	73.5 x 40 x 185 mm
Input	1200W: 100-127Vac / 50-60Hz 1600W: 200-240Vac / 50-60Hz 1600W: 0240Vdc / 50-60Hz (for CQC only)
+12V	Max: 100A / Min: 0A (100Vac-127Vac) Max: 133.3A / Min: 0A (200Vac-240Vac)
12V SB	Max: 3A / Min: 0A
Output Type	Backplanes (gold finger)

Operating Environment

RoHS	RoHS Compliant
Environmental Spec.	Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -30°C to 60°C (-30°F to 140°F) Operating Relative Humidity: 8% to 80% (Non-Condensing) Non-operating Relative Humidity: 8% to 90% (Non-Condensing)

Environmental / Recycling

Recycle	Return Server-End of Life Product